



Locker Inspection and Maintenance Instructions

1. Periodic Inspections

- 1.1 Frequency of inspection: annual
- 1.2 Specific items for annual inspection
 - a. Operation of door-open and close door in normal fashion and note ease of operation.
 - b. Observe any missing or loose parts such as handles, coat hooks, or bolts and nuts.

2. Maintenance

- 2.1 Routine maintenance procedures
 - a. Lubricate the frame hooks located on the vertical jamb member with a solidified lubricant.
 - b. Lubricate lock bar in door at the lock bar guides (wipe off excess lubricant).
 - c. Insure the frame hooks clear the opening in the door when closing the door-hold handle in the "up" position while closing door to observe the requirement. Adjust frame hook with pliers if any part of the frame hook comes in contact with door.
 - d. Tighten any loose nuts or fasteners on handles, and/or body parts, including coat hooks.
 - e. Clean exterior and interior of locker.
- 2.2 Products to use
 - a. Lubricant-"Doorease" or equivalent on frame hooks, "WD40" on the lock bar guides.
 - b. Cleaning fluids-mild detergent followed with clear water rinse and dry. (see attached acceptable cleaner list)
 - c. Touch-up paint-as supplied by Republic-please specify color.
 - d. Tools-3/8" hex driver for tightening nuts on body.
1/4" hex nut driver for tightening handle screws on #12 lift handle.

3. What to do if damaged or missing parts cannot be purchased locally or repaired by local vendors.

- 3.1 Contact: Republic Storage Systems, LLC
Attention: Sales Administration Department
1038 Belden Avenue NE
Canton, Ohio 44705 U.S.A.
www.republicstorage.com
- 3.2 Retain installation drawings and shipping bills of material for reference for possible part replacement





Republic Spray and Dip Finish Acceptable Cleaners

Acceptable cleaners for the Republic's Spray and Dip finishes include:

- ammonia-based household cleaners (Windex, Glass Plus, 10 ammonia in water)
- diluted floor cleaners (Lysol, Mr. Clean, Pine Sol)
- chlorine-based bleach and water solutions (less than 3 bleach)
- mild dish soaps and dissolved laundry detergents (Dawn, Palmolive, Tide, Wisk)
- aliphatic solvents for oil and grease removal (mineral spirits, VM&P Naphtha)

All units cleaned should be rinsed with water and dried with a soft towel.

The following cleaners should **NOT** be used on any spray or dip paint finish:

- abrasive cleaners - these cleaners contain abrasive particles which will mar the surface and cause degradation of the coating (Soft Scrub, Comet, rubbing or polishing compounds)
- aromatic or strong organic solvents - these solvents can remove and soften the coating surface and cause a dulling to the gloss (xylene, toluene, lacquer thinner, methylene chloride, acetone and other ketones)
- acidic cleaners - these will penetrate and soften the coating causing lack of adhesion and protection (Lime Away, hydrochloric and muratic acid, other acid compounds)
- alkaline cleaners - these cleaners will etch and soften the coating (Lye, caustic cleaners, toilet bowl cleaners)
- hydrogen peroxide based cleaners - these cleaners are incompatible with metals and testing has proven them to be caustic to the parts

Sources: Jamestown Paint Company
Valspar Paint Manufacturing Co.
PPG Industries, Inc.

